

Certificate of Compliance

Certificate Number:

UL-US-L199260-22-
11107002-9

Report Reference:

E199260-20070111

Issue Date:

2025-02-24

Issued to:

BIMED TEKNIK ALETLER SAN TIC A S
Deliklikaya Mah. Yuzbasi Mehmet Hilmi Cad. No:28 Ic Kapı No:1,
Arnavutkoy, ISTANBUL, 34555, TR

This certificate confirms that representative samples of:

QCRV2 - Outlet Bushings and Fittings - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

UL 514B, 6th Ed., Issue Date: 2012-07-13, Revision Date: 2020-05-22

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L199260-22-11107002-9
Report reference E199260-20070111
Date 2025-02-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BMBC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-E1 (M16T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-ES (M12T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNBC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNBC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L199260-22-11107002-9
Report reference E199260-20070111
Date 2025-02-24

BNBC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-E1 (NPT3/8"T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-ES (NPT1/4"T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNSC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNSC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNSC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBC-02, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBC-03, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBE-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBE-02, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBE-03, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSSC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSSC-02, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSSC-03, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:

UL-CA-L199260-42-
11107002-7

Report Reference:

E199260-20070111

Issue Date:

2025-02-24

Issued to:

BIMED TEKNIK ALETLER SAN TIC A S
Deliklikaya Mah. Yuzbasi Mehmet Hilmi Cad. No:28 Ic Kapı No:1,
Arnavutkoy, ISTANBUL, 34555, TR

This certificate confirms that representative samples of:

**QCRV8 - Outlet Bushings and Fittings Certified for Canada -
Component**

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 NO. 18.3-12, 2nd Ed., Issue Date: 2012-07-01,
Revision Date: 2020-05-22

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L199260-42-11107002-7
Report reference E199260-20070111
Date 2025-02-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BMBC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBC-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMBE-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-E1 (M16T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMEM-ES (M12T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-E1, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BMSC-ES, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNBC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNBC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L199260-42-11107002-7
Report reference E199260-20070111
Date 2025-02-24

BNBC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-E1 (NPT3/8"T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNEM-ES (NPT1/4"T), , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNSC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNSC-01S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BNSC-0S, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBC-02, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBC-03, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBE-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBE-02, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSBE-03, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSSC-01, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSSC-02, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating
BSSC-03, , may be followed by (LF)	Liquid-tight flexible cord fittings, type 1, 4X, 12, and 13 rating



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.